



# Acid Car Kit

## PRESSURE RELIEF VALVE

- Unique constant-force spring technology
- Low profile external design
- Valve components protected from commodity
- Field repair or replacement
- High flow capacity

### PRV Specifications

Flange: 6" or 10" diameter

Flange thickness: 1.125"

Interface: flat, tongue & groove  
or raised

Material: carbon or stainless

PSI: 75 or 165

AAR approval: 079004



## ONE-BOLT MANWAY

- Eliminates eye-bolt leaks and NARs
- Low profile design
- Gasket replacement is minimal
- 5 minute open/close adds loading efficiency
- Worker safety features

### Manway Specifications

Nozzle length: 5 3/8" to 15"

Material: carbon or stainless

Closure: one-bolt

Loading: universal adapter

AAR approval: E119023



## VACUUM RELIEF VALVE

- Unique constant-force spring technology
- Flat gasket seal eliminates O-rings
- Seal welded stem increases longevity
- Valve components protected from commodity
- Optional baffle
- Stainless steel body

### VRV Specifications

PSI: 4.5  
 Height: 5.33"  
 Flange thickness: 0.625"  
 Connection: 2" flanged  
 AAR approval: E152103



## BOTTOM OUTLET VALVE

- Unique ceramic ball/wiper technology
- Withstands extreme temperatures & corrosion
- Easy-turn handle is AAR approved
- Stainless steel or carbon body
- Ceramic or stainless ball

### BOV Specifications

Max PSI: 275  
 Temperature: 400° to -40°  
 Height: 5.41"  
 Flange thickness: 0.94"  
 Port: 4" (full)  
 AAR approval: E162100



**GAUGING  
 DEVICE**