




# Pressure Car Kit

## PRESSURE-CAR PRESSURE RELIEF VALVE

- Superior constant-force spring technology
- Low profile external design
- Valve components protected from commodity
- Field repair or replacement



(Coverless view)

### Specifications

Material: carbon or stainless  
 Pressure: 280.5 or 330 psi  
 Rating: to 500psi

## ANGLE VALVE

- Universal use; no wetted or outlet O-rings
- Self-draining, self-cleaning seat
- Low operating torque for ease of use
- Casting or non-casting available
- Adjustable live-loaded packing
- Options for pipe-plug construction



### Specifications

Material: carbon or stainless  
 Rating: to 500psi  
 Connection: 2" NPT

## CHECK VALVE

### Specifications

Material: carbon or stainless  
 Size: 2" (66GPM-H<sub>2</sub>O) and 3" (284GPM-H<sub>2</sub>O)  
 Style: float  
 Seat: removable



## NEEDLE VALVE

### Specifications

Material: stainless steel  
 Temperature: 350°  
 Pressure: 1,500psi  
 Connection: 3/4" in; 1/4" out (male/female options)  
 Options: 1/4" plug, chain; flanged or threaded

## MAGNETIC GAUGING DEVICE & ROD

### Specifications

Material: stainless steel  
 Rods: 1, 2 or 3 scale  
 Float: 7.5" diameter  
 Flange: carbon or stainless  
 Scale unit: inches and/or mm



## THERMOMETER WELL

### Specifications

Material: carbon or stainless  
 Temperature: 350°  
 Seals: easily replaceable  
 Options: flanged, threaded

Installation manuals available online or by request.